



Digital Keypad Safe with Audit Trail

OS300

- User Friendly
- 6-Digit Display
- Fluoropad™ Keypad
- 4 or 6-Digit Code
- ADA Compliant
- "Code to Close" Technology
- Programmable Shut Down Mode
- Non-Resident Master Code
- Audit Trail records the last 960 Operations
- Insertion Protected Door
- Reinforced Bolt Frame
- 2 Solid Steel Bolts
- Anti-Drill Rotating Bolts
- Anti-Theft Labyrinth Mechanism
- Portable Programmer Password Protected
- Printer with Double Signature Panel - Optional
- 4 AA Batteries
- Low Consumption Motor
- Power Status Display
- Senerlink™ Interface - Optional
- Available in 7 sizes
- Flash Technology for future upgrades



The OS300 is Onity's most feature enhanced electronic in-room safe. Its user friendly operation for both guests and staff coupled with a high level of reliability and functionality makes it an ideal safe for any property.

OS300 Extended Portable Programmer (XPP)

- Non-Resident Master Code
- Emergency Power Openings
- Password Protected
- User Friendly, Large Display with Hot Key Menus
- Manages up to 250 Users
- Records the last 6,550 Operations
- Auto shut-off

OS300 Features

● Standard ○ Optional N/A Not Applicable

MECHANICAL FEATURES

- Corrosion/Scratch Resistant Finish ●
- Left Hinges ○
- Spring Loaded Door ●
- Two Solid Steel Bolts ●
- Anti-Drill Rotating Bolts ●
- Insertion Protected Door ●
- Bolt-Side Reinforced Mechanism ●
- Anti-Theft Labyrinth Mechanism ●
- Door Mounted Mechanism ●
- Replaceable Mechanism ●
- Tamper Proof Screws ●
- Digital Display ●
- Fluoropad™ Keypad ●
- Heavy Duty Depression Keypad ●
- ADA Compliant Keypad ●
- Inside Shelf (Suite Size Only) ○
- Pedestal ○
- Decorative Handle ●

PERFORMANCE FEATURES

- 4-Digit Code ●
- 6-Digit Code ○
- Buzzer Signal ●
- Real Time Clock ●
- 'Code to Close' Technology ●
- 4 LR6 AA 1.5V Batteries ●
- Low Consumption Motor ●
- #Operations with 4 AA 10,000
- Power Status Indicator ●
- Audit Trail/# Operations Recorded 960
- Portable Unit XPP
- Portable Unit/Password Protected ●
- Portable Printer ○
- Emergency Power Supply ●
- Shut Down Mode ●
- Programmable Shut Down Mode ●
- Non-Resident Master Code ●

SERVICE

- Onity Worldwide Service ●

COMPATIBILITY/INTERFACE

- Onity Senerlink™ Interface ○

SIZES/FINISHES

- Suite Size ●
- Business Size ●
- Laptop Size ●
- Mini Size ●
- Wall Size ○
- Resort Size ○
- M Size ○
- Ivory Finish ●
- Matte Black Finish ●



External Dimensions

	Suite Safe		Business Safe		Laptop Safe		Mini Safe	
Height:	570 mm	22,43 In	204 mm	8,03 In	204 mm	8,03 In	204 mm	8,03 In
Width:	424 mm	16,69 In	424 mm	16,69 In	424 mm	16,69 In	424 mm	16,69 In
Depth:	390 mm	15,35 In	460 mm	18,10 In	370 mm	14,56 In	220 mm	8,66 In
Volume:	81,5 Lts	21,5 Gal	38,6 Lts	10,2 Gal	31 Lts	8,2 Gal	18,15 Lts	4,9 Gal
Weight:	30 kgs	65,93 lbs	17 kgs	37,36 lbs	15,5 kgs	34,07 lbs	12 kgs	26,37 lbs

© Onity April 2003. All rights reserved. Data subject to change without notice. TESA is a licensed brand of Talleres de Escorialaza, S.A.



Onity

'innovative thinking'

TESA Entry Systems

Extended Portable Programmer (XPP)

Extended Portable Programmer (XPP)

- Non-Resident Master Code
- Emergency Power Openings
- Safes diagnosis
- Password Protected: individual user log-in
- User friendly, heavy-duty ADA compatible membrane keypad
- Alphanumeric keypad with hot key menus
- Portable size, able to be operated with one hand
- Large display 8*20 characters
- Messages in different languages - optional
- Buzzer for acoustic communication with user
- Manages up to 250 users
- Safes Audit Trail on screen
- Safes Audit Trail printable in the guestroom with optional portable printer
- Double signature panel for hotelier and guest
- XPP Audit records the last 6,550 operations
- Fast charge of batteries, within 1 hour
- Low-power detection
- Anti-theft protection sequential code
- Auto shut-off



Characteristics:

Case material: grey ABS

Dimensions:

250 mm length / 108 mm width / 42 mm height
8.07 in length / 4.25 in width / 1.65 in height

Weight:

375 gr / 0.827 lb without batteries
490 gr / 1.02 lb with batteries

Operating voltage: 6 VDC supplied by 4 AA rechargeable or alkaline batteries or AC/DC adaptor



Onity

'innovative thinking'

TESA Entry Systems

Portable Printer (Optional)

Portable Printer (Optional)

- Direct thermal printing system
- Recommended paper: TF50-KS-E2D (Nippon paper)
- Serial interface
- LED color for Power and Charge
- Operation keypad
- Battery type: Li-ion battery pack
- Battery charging time: Approximately 3 hours by main unit + AC adapter
- Auto shut-off
- AC Adapter:
 - 10AD-JU (for Japan, USA, and Canada)
 - 10AD-E (for Europe)
 - Input voltage 90 V - 264 V AC
 - Output voltage 9.0 V DC 1.0 A
- Operating Environment:
 - Temperature: 5 - 40°
 - Humidity: 35 - 80% RH (No dew condensation)



Characteristics:

Dimensions:

116 mm width / 90 mm depth / 51 mm height
 4,57 in width / 3,54 in depth / 2 in height
 Paper cover width: 57 mm / 2,24 in

Weight:

Approx. 370 g / 0.81 lb
 With battery and belt clip, without paper